Product Information



Jowat Edgebanding Adhesives









Versatile hot melt adhesives for edgebanding

- High resistance to heat and water
- Excellent bond strengths and zero-bondline appearance
- Wide range of applications, for all edgebanding materials established on the market

Jowat Adhesives

The Cutting Edge: High-End Results, Low-End Effort

For those who aim for unparalleled furniture quality, Jowat supplies a comprehensive portfolio of edgebanding adhesives. Jowatherm® PUR hot melt adhesives are the top choice for seamless bondlines, high-strength bonding and highest resistances to heat and moisture.
Do you want to impress your customers and at the same time ensure a low-maintenance and uncomplicated production process? Draw from the wealth of Jowatherm® EVA hot melt adhesives or benefit from the high heat resistance of Jowatherm® PO technology.
Edgebanding adhesives from Jowat are renowned for a broad spectrum of adhesion to different materials, good initial strength and clean processing. Specialist adhesives from Jowat: Tailor-made for your application.

Jowat Edgebanding Adhesives

Versatile hot melt adhesives for edgebanding

	Jowatherm® PUR 607.40	**Jowatherm® PUR 608.00**	**Jowatherm® 280.30**	**Jowatherm® 288.60**	**Jowatherm® PO 237.50**
Based on	PUR	PUR	EVA	EVA	PO
Appearance	beige, white, pure white	colorless, white	yellow translucent	beige, white	colorless
Processing temperature	130°C–150°C	100°C–120°C	180°C–200°C	180°C–200°C	190°C–210°C
Oxidation stability	-	-	●●◐	●●○	●●◐
Crosslinking speed	●○○	●◐○	-	-	-
Heat resistance	●●●	●●●	●◐○	●◐○	●●◐
Water resistance	●●●	●●●	●◐○	●○○	●●○
Feed speed	●●◐	●●○	●●○	●◐○	●●○
Yield	●◐○	●●●	●●●	●◐○	●●●

The information given in this leaflet is based on test results from our laboratories as well as on experience gained in the field, and does in no way constitute any guarantee of properties. Due to the wide range of different applications, substrates, and processing methods beyond our control, no liability may be derived from these indications nor from the information provided by our free technical advisory service. Before processing, please request the corresponding data sheet and observe the information in it! Customer trials under everyday conditions, testing for suitability at normal processing conditions, and appropriate fit-for-purpose testing are absolutely necessary. For the specifications as well as further information, please refer to the latest technical data sheets.